



SAFETY DATA SHEET

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier**Product Name**

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Other means of identification**Synonyms**

No information available

Recommended use of the chemical and restrictions on use**Identified uses**

Lubricant

Uses advised against

Consumer use

Details of the supplier of the safety data sheet**Manufacturer**

Lubrication Engineers Inc.
1919 E. Tulsa
Wichita, KS 67216
USA
800-537-7683

Emergency Telephone Number

CHEMTREC: 1-800-424-9300 (NORTH AMERICA)
+1-703-527-3887 (INTERNATIONAL)

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label Elements

Emergency Overview

Signal Word

None

Hazard Statements

None

The product contains no substances which at their given concentration, are considered to be hazardous to health

appearance red

Physical state Paste

Odor Hydrocarbon-like

Precautionary Statements - Prevention

None.

Response

None.

Eyes

None.

Skin

None.

Inhalation

None.

Ingestion

None.

Fire

None.

Spill

None.

Storage

None.

Disposal

None.

Hazards not otherwise classified (HNOC)

None

- May be harmful in contact with skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
---------------	---------	----------

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

Residual oils (petroleum), solvent dewaxed	64742-62-7	80 - 90
Propylene carbonate	108-32-7	1 - 5
Butylated Hydroxy Toluene	128-37-0	0.1 - 1

The producer of "1250" declares that it contains less than 3% DMSO extractable material by IP-346

4. FIRST AID MEASURES

First Aid Measures

General Advice	If symptoms develop move victim to fresh air. Show this safety data sheet to the doctor in attendance. Do not breathe dust/fume/gas/mist/vapors/spray.
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. Call a physician if irritation persists.
Skin Contact	Consult a physician if necessary. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Protection of First-aiders	Use personal protective equipment.

Most important symptoms and effects, both acute and delayed

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point	287 °C / 548.6 °F
Suitable Extinguishing Media	Water spray, Carbon dioxide (CO2), Foam, Dry chemical
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.
Specific Hazards Arising from the Chemical	Thermal decomposition can lead to release of irritating gases and vapors.
Explosion Data	
Sensitivity to Mechanical Impact	Not impact sensitive.
Sensitivity to Static Discharge	May be ignited by friction, heat, sparks or flames.
Protective Equipment and Precautions for Firefighters	Wear self-contained breathing apparatus and protective suit.

NFPA

Health hazard 1

Flammability 1

Stability 1

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Do not touch or walk through spilled material. Remove all sources of ignition.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

Methods for Cleaning up Use personal protective equipment. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Prevent vapor buildup by providing adequate ventilation during and after use. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products. Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Silica, quartz 14808-60-7	TWA: 0.025 mg/m ³	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³	IDLH: 50 mg/m ³ TWA: 0.05 mg/m ³
Butylated Hydroxy Toluene 128-37-0	TWA: 2 mg/m ³	(vacated) TWA: 10 mg/m ³	TWA: 10 mg/m ³
Mica (mineral) 12001-26-2	TWA: 3 mg/m ³	(vacated) TWA: 3 mg/m ³	IDLH: 1500 mg/m ³ TWA: 3 mg/m ³
Titanium Dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ (vacated) TWA: 10 mg/m ³	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ TWA: 0.3 mg/m ³
Iron Oxide 1309-37-1	TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³ TWA: 5 mg/m ³ (vacated) TWA: 10 mg/m ³ (vacated) TWA: 5 mg/m ³	IDLH: 2500 mg/m ³ TWA: 5 mg/m ³
Methyl alcohol 67-56-1	STEL 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

		(vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	STEL: 250 ppm STEL: 325 mg/m ³
--	--	--	--

Appropriate engineering controls

Engineering Measures Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tightly fitting safety goggles.

Skin and Body Protection Long sleeved clothing. Protective gloves.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Paste
appearance red
Odor Hydrocarbon-like
Odor threshold No information available

Property

<u>Property</u>	<u>Property</u>
pH	6 - 8
Melting Point / Freezing Point	No data available
Boiling Point/Range	no data available
Flash Point	287 °C / 548.6 °F
Upper flammability limit:	No data available
Lower Flammability Limit	No data available
Vapor pressure	No data available
Vapor Density	< 1 (Air = 1)
Specific Gravity	0.95
Water solubility	negligible
Partition Coefficient: n-octanol/water	no data available
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Viscosity, kinematic	not applicable

10. STABILITY AND REACTIVITY

reactivity No information available

Chemical stability Stable under recommended storage conditions.

Possibility of Hazardous Reactions None under normal processing.

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

Conditions to Avoid Heat, flames and sparks. Contact with other chemicals

Incompatible Materials Strong oxidizing agents. Strong acids. Strong bases.

Hazardous Decomposition Products Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke)

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information
Inhalation	May cause irritation of respiratory tract.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	May cause irritation.
Ingestion	There is no data available for this product.

Component Information

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Residual oils (petroleum), solvent dewaxed 64742-62-7	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2.18 mg/L (Rat) 4 h
Propylene carbonate 108-32-7	= 29000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Butylated Hydroxy Toluene 128-37-0	> 2930 mg/kg (Rat)	> 2000 mg/kg (Rat)	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

The producer of "1250" declares that it contains less than 3% DMSO extractable material by IP-346

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

Target Organ Effects Skin, Central nervous system (CNS), Respiratory system, Eyes, Liver.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

ATEmix (oral) 5202 mg/kg
 ATEmix (dermal) 2067 mg/kg
 ATEmix (inhalation-dust/mist) 48.4 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to daphnia and other aquatic invertebrates
Residual oils (petroleum), solvent dewaxed 64742-62-7	-	LC50> 5000 mg/L Oncorhynchus mykiss 96 h	-	EC50 > 1000 mg/L 48 h
Propylene carbonate 108-32-7	EC50 > 500 mg/L 72 h	LC50> 1000 mg/L Cyprinus carpio 96 h LC50= 5300 mg/L Leuciscus idus 96 h	EC50 > 10000 mg/L 17 h	EC50 > 500 mg/L 48 h
Butylated Hydroxy Toluene 128-37-0	EC50 = 6 mg/L 72 h EC50 > 0.42 mg/L 72 h	-	-	-

Persistence and Degradability No information available.

Bioaccumulation

.

Mobility

The product is insoluble and floats on water.

Chemical name	Log Pow
Methyl alcohol 67-56-1	-0.77

Other Adverse Effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods

Dispose of in accordance with local regulations.

Contaminated Packaging

Do not re-use empty containers. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol 67-56-1		Included in waste stream: F039		ignitable waste

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical name	California Hazardous Waste Status
Methyl alcohol 67-56-1	Toxic Ignitable

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Not determined
NDSL	Complies
EINECS	Not determined
ELINCS	Not determined
ENCS	Not determined
IECSC	Complies
KECL	Not determined
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	67-56-1	3e-005	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

SDS: 1250

1250 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 01-08-2021

Revision Number 5

CERCLA

This material does not contain any components with a CERCLA RQ.

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl alcohol 67-56-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Prop. 65
Silica, quartz - 14808-60-7	Carcinogen
Titanium Dioxide - 13463-67-7	Carcinogen
Methyl alcohol - 67-56-1	Developmental

U.S. State Right-to-Know Regulations

This product does not contain any substances regulated by state right-to-know regulations

NFPA

Health hazard 1

Flammability 1

Stability 1

16. OTHER INFORMATION

Issuing Date 04-24-2012
Revision Date 01-08-2021
Reason for revision Formulation.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SDS is available at www.LElubricants.com**End of Safety Data Sheet**